10/066,793

Applicants: DEL BECCARO et al.

Serial No. 10/066,793

ph

Alternatively, transmission system 170 does not perform step 376. Rather, if it is determined that Buy button 250 and/or Buy-Previous button 251 should be included in the video image created in step 372, then transmission system 170 sends one or more commands to receivers 180 that direct the receivers 180 to overlay Buy button 250 and or Buy-Previous button 251 onto the video image transmitted in step 378, provided that receivers 180 are capable of overlying selectable buttons.

The paragraph beginning at line 23 of page 17 has been amended as follows:

•

In step 504, video subsystem 104 parses the trigger message to determine the sound recording identifier, sound recording information, and channel identifier specified therein. Next (step 506), video subsystem 104, uses the pre-defined configuration data to determine a set of assets identifiers that are associated with the sound recording identifier last determined in step 504. Video subsystem 104 then determines the screen position that is associated with each asset identifier in the set (step 508). The asset identifiers determined in step 506 and their associated screen positions determined in step 508 are included in the data packet (step 510).

BSH 6/82/07

The paragraph beginning at line 18 of page 22 has been amended as follows:

Referring now to process 900, process 900 begins in step 902, where video image generator 702 waits to receive from video subsystem 104 a data packet 732, which comprises a video image specification. When a data packet 732 is received, control passes to step 904, where video image generator 702 parses the video image specification contained in the data packet 732 to determine the set of asset identifiers specified therein and the screen positions associated with each asset identifier. After step 904, control passes to step 906.

Ab